

# CLASS B EPIRBs



The Guest Class B EPIRBs are a necessary part of every vessel's safety gear. Model 630A and the Micro B transmit simultaneously on two international distress frequencies: 121.5 MHz and 243 MHz. These unique signals can be detected by aircraft, ships, and the COSPAS/SARSAT satellite system. The combined earth and space monitoring system provides assurance that your distress signal will be detected and pinpointed so that search and rescue forces can be quickly deployed. Continuous transmission provides a homing signal for speedy recovery time.

### Model 630A

Using two antennas to maximize signal strength on earth frequency, the energy-efficient circuitry permits long duration transmissions. Comes complete with a replaceable 3-year alkaline battery.

### Model 953 Micro B

The smallest Class B EPIRB available, Model 953 features a 2-year product warranty and a powerful 5-year lithium battery. Designed to be disposable after 5 years, the Micro B operates at temperatures as low as -20°C.



## CLASS B EPIRB FEATURES

- ☑ Simultaneous transmission on 121.5 & 243 MHz
- ☑ Choice of replaceable 3-yr. alkaline battery (Model 630A) or 5-year permanent battery (Model 953)
- ☑ Wide operating temperature range (-20°C to 55°C)
- ☑ Meets FCC requirements for improved satellite detection
- ☑ Can be handheld, floated on water, or attached to a liferaft or personal flotation device
- ☑ Engineered and constructed with Guest's traditional regard for dependability
- ☑ Full factory product support

### Optional Accessories

		Part #
630A	Stainless steel storage bracket	U-2553
630A	Replacement 3 year battery	U-3150P
953	Mounting Bracket	95320000-01-P
953	Flotation collar	95310200-01-P

Model	Frequency (MHz)	Output Power	Operating Life	Emission	Frequency Stability	Activation	Battery	Dimensions	Weight
630A	121.5 & 243	400mW/channel	48 hrs. min at -20°C	A3N	.005%	Manual On/Off	Replaceable 3-yr. alkaline	14"H x 5"	4 lbs.
953 Micro B	121.5 & 243	75mW/channel	48 hrs. min at -20°C	A3X	.005%	Manual On/Off	Permanent 5-yr. lithium	4.5"H x 2.5"	12 oz.
952-01 (CAT II)	406.025 & 121.5	5W 25mW	48 hrs. min at -20°C	G1D & A3N	<2 x 10 <sup>-9</sup>	Automatic float-free	Replaceable 6-yr. lithium	14.6"H x 5.56"	10 lbs.