


# Chain

Trade Size	Proof Coil Chain / Grade 30				
	Working Load Limit in Pounds	Feet per Drum	Feet per 1/2 Drum	Minimum Weight per Foot	Maximum Length per 100 Links
1/8"	375		1,000	.17	90.5"
3/16"	800	1,600	800	.33	96.4"
1/4"	1,300	800	400	.63	124.0"
5/16"	1,900	550	275	.93	129.1"
3/8"	2,650	400	200	1.41	137.8"
1/2"	4,500	200	100	2.40	179.1"
5/8"	6,900	150	75	3.58	220.5"
3/4"	10,600	100	50	5.48	275.6"
7/8"	12,800	75	35	7.31	258.7"
1"	13,950	60	30	9.41	278.8"

## Proof Coil Chain


Grade 30/ Self Colored-Zinc Plated-Hot Galvanized



Trade Size	Long Link Chain / Grade 30				
	Working Load Limit in Pounds	Feet per Drum	Minimum Weight per Foot in Pounds	Inside Length Inches per Link	Inside Width Inches per Link
1/2"	4,500	200	2.55	2.00	.88
5/8"	6,900	150	3.50	2.56	1.0

## Long Link Chain


Grade 30/ Galvanized



Trade Size	High Test Chain / Grade 43				
	Working Load Limit in Pounds	Feet per Drum	Feet per 1/2 Drum	Minimum Weight per Foot	Maximum Length per 100 Links
1/4"	2,600	800	400	.63	124.0"
5/16"	3,900	550	275	.93	129.1"
3/8"	5,400	400	200	1.41	137.8"
1/2"	9,200	200	100	2.40	179.1"
5/8"	11,500	150	75	3.58	220.5"
3/4"	16,200	100	50	5.48	275.6"

## High Test Chain

Grade 43/ Self Colored-Hot Galvanized



Trade Size	Transport Chain / Grade 70 Plated				
	Working Load Limit in Pounds	Feet per Drum	Feet per 1/2 Drum	Minimum Weight per Foot	Maximum Length per 100 Links
1/4"	3,150	800	400	.63	124.0"
5/16"	4,700	550	275	.93	129.1"
3/8"	6,600	400	200	1.41	137.8"
1/2"	11,300	200	100	2.40	179.1"

## Transport Chain

Grade 70 Plated



Trade Size	Alloy Chain / Grade 80				
	Working Load Limit in Pounds	Approx. Weight per 100 Ft. in Lbs.	Actual Material Diameter	Inside Length	Inside Width
9/32"	3,500	72	.281	.88	.40
3/8"	7,100	150	.397	1.22	.57
1/2"	12,000	261	.520	1.56	.775
5/8"	18,100	361	.630	1.93	.87
3/4"	28,300	540	.750	2.02	.97
7/8"	34,200	713	.875	2.27	1.14
1"	47,700	948	1.000	2.67	1.35

## Alloy Chain

Grade 80

