


Western[®] Malleable Iron Shell Blocks

FOR MANILA ROPE

These blocks have Malleable Iron Shells and both outside and inside straps extend full length of shell. Ends of center pin are flush with sides of shell. Malleable Iron Blocks are standard equipment with Public Utility Companies.



HS-301-B
SINGLE



N-302-B
DOUBLE



P-303-B
TRIPLE

Block Size (in.)	Fitting	Single Sheave		Double Sheave		Triple Sheave	
		301 B Stock No. Galv.	301 R Stock No. Galv.	302 B Stock No. Galv.	302 R Stock No. Galv.	303 B Stock No. Galv.	303 R Stock No. Galv.
4	HS	680971	680775	681373	681177	681774	681578
6	HS	680999	680793	681391	—	681792	—
8	HS	681015	680819	681417	—	681818	—
4	N	682639	682434	683031	—	683433	—
6	N	682675	—	683077	—	683479	—
8	N	682719	—	683111	—	683512	—
4	P	691031	—	692637	—	694234	—
6	P	691077	—	692673	—	694270	—
8	P	691111	—	692717	—	694314	—

Bearing Code: B — Self Lubricating Bronze Bushed, R — Roller Bearing.

SEE APPLICATION AND WARNING INFORMATION

Block Size (in.)	Sheave Size (in.)		Manila Rope Size (in.)	Working Load Limit * (lbs.)			Weight Each (lbs.)		
	Outside Diam.	Rim Thickness		Single	Double	Triple	Single	Double	Triple
4	2.25	.63	1/2	1100	1600	2200	2.25	3.75	5.00
6	3.50	1.00	3/4	2000	3300	4000	5.50	9.25	12.50
8	4.75	1.13	1	3300	5100	7000	10.00	16.50	22.00

* Ultimate Load is 3.5 times the Working Load Limit.