

## Sash Cord

### SPOT CORD® SASH CORD

America's finest quality and best performing cotton\* sash cord for over 100 years.

\*Blended cotton/polyester yarn

- High strength composite cotton\* cover wears longer
- High tenacity nylon core adds extra strength and reduces stretch
- Coating provides chemical, weather and heat resistance
- Recognized as the strongest, longest lasting of all sash cords...for maximum customer value and satisfaction

No.	Size		Working Load Lbs	Strength** Lbs
	Dia.			
6	3/16"		105	700
7	7/32"		124	825
8	1/4"		150	1,000
9	9/32"		214	1,425
10	5/16"		240	1,600
12	3/8"		300	2,000
14	7/16"		465	3,100
16	1/2"		540	3,600

Product Code	Size No.	Put-Up	Weight Lbs
001-060-05	6	100' Hank	14.5
001-070-03	7	50' Hank	9.0
001-070-05	7	100' Hank	18.0
001-070-71	7	1,200' Spool	18.0
001-080-03	8	50' Hank	11.5
001-080-05	8	100' Hank	23.0
001-080-89	8	1,000' Display Coil	19.0
001-080-71	8	1,200' Spool	23.0
001-080-75	8	2,400' Spool	47.0
001-090-05	9	100' Hank	29.0
001-100-05	10	100' Hank	34.0
001-100-71	10	1,200' Spool	34.0
001-120-05	12	100' Hank	49.0
001-120-71	12	1,200' Spool	49.0
001-140-05	14	100' Hank	32.0
001-160-05	16	100' Hank	42.0

Standard Pack: #6 through #12 - 12 connected hanks, 1 spool or 1 coil per case  
#14 through #16 - 6 connected hanks or 1 spool per case.

\*\*All strengths depicted are average rope strength developed without knotted or mechanical terminations. The strength reduction caused by knotted, mechanical or other methods of termination should be considered when selecting an appropriate size rope for a particular application.

### AETNA™ SASH CORD

A quality cotton\* sash cord, superior in strength, durability and reputation to virtually all other sash cords except Samson Spot Cord.

\*Blended cotton/polyester yarn

- Balanced interlocked solid braid retains smooth, round construction
- High durability composite cotton\* cover
- Reinforcing synthetic core
- Polished to resist rot, mildew and wear
- Excellent performance
- Strong brand name recognition

No.	Size		Working Load Lbs	Strength** Lbs
	Dia.			
6	3/16"		79	525
7	7/32"		94	625
8	1/4"		120	800
10	5/16"		203	1,350
12	3/8"		255	1,700
14	7/16"		360	2,400
16	1/2"		465	3,100

Product Code	Size No.	Put-Up	Weight Lbs
021-060-05	6	100' Hank	14.5
021-070-03	7	50' Hank	9.4
021-070-05	7	100' Hank	18.0
021-070-71	7	1,200' Spool	18.7
021-070-86	7	1,200' Display Coil	18.7
021-080-03	8	50' Hank	11.4
021-080-05	8	100' Hank	23.0
021-080-89	8	1,000' Display Coil	19.0
021-080-71	8	1,200' Spool	23.0
021-100-05	10	100' Hank	35.0
021-120-05	12	100' Hank	50.0
021-120-71	12	1,200' Spool	50.0
021-140-05	14	100' Hank	32.0
021-160-05	16	100' Hank	44.0

Standard Pack: #6 through #12 - 12 connected hanks, 1 spool or 1 coil per case  
#14 through #16 - 6 connected hanks or 1 spool per case.

\*\*All strengths depicted are average rope strength developed without knotted or mechanical terminations. The strength reduction caused by knotted, mechanical or other methods of termination should be considered when selecting an appropriate size rope for a particular application.