

General Safety Belts & Accessories For: Industrial & Construction Workers

Now Also Available—Polyester Webbing. To order use P designation before Model Number. *Example:* No. P000.

NO. 747 NYLON BELT with Rope Lanyard

Our extremely popular general maintenance and construction worker's belt is fitted with drop forged steel "D" rings; one "D" ring is spliced with a 10' long, 1/2" diameter nylon rope, fitted with No. 3031 drop forged steel snap hook. 1 3/4" wide nylon webbing with 3" wide nylon body pad, 9,500 lb. test, is resin or latex treated for abrasion resistance.

NO. 745 NYLON BELT

Same as No. 747, but with 6 foot lanyard.

NO. 746 NYLON BELT

Same as No. 747, but without rope lanyard.

NO. 758 NYLON BELT

Same as No. 746, but with additional "D" ring located at wearers back.

NO. 756 NYLON BELT

Same as No. 746, but with only one "D" ring located at wearers back.



NO. 743 NYLON BELT With Friction Buckle

ALL-NYLON belt is made of 1 3/4" wide, 9,500 lb. test, nylon webbing and fitted with friction-type buckle. Standard with two "D" rings. For belt with only one "D" ring specify No. 744.



NO. 752 NYLON BELT Used on Swinging Scaffolds

Used primarily on swinging scaffolds. Belt has "D" ring at back for securing to independent life line. Belt features a 4" wide, nylon abdominal pad for comfort and load distribution. Belt is commonly used with our Series 2100 or 2200 1/2" nylon lanyards, usually not more than 6' long. For lanyards refer to page 9.

NO. 753 NYLON BELT

Nylon belt same as No. 752, but with a 6 foot, 1/2 inch nylon rope lanyard, spliced to "D" ring. Fitted with our No. 3031 snap hook.

NOTE: Belts illustrated are fitted with circular "D" ring for added protection and safety.



All nylon belts are lock-stitched with nylon thread.

***Using vertical life lines and lanyards with your belts?**

BELT SIZE CHART

Ordering Code	Belt Size
Ex Small	28-36
Small	32-40
Medium	36-44
Large	40-48
Ex Large	44-52
Outer Clothing Should Be Considered	