

# NAVIGATION LIGHTS

FOR USE ON VESSELS UNDER 20 METERS (65.6 FT.) IN LENGTH.

## FEATURES

### TOP MOUNT. BLACK PLASTIC.

WITH STAINLESS STEEL MOUNTING BRACKET

COMPLETE WITH 12, 24 OR 32 VOLT BULB.

Height Overall Inches	Projection Inches	Height Lens Inches	Screw Size	Weight Ounces
4-13/16	3-5/16	2-3/4	8	12-1/2

## ORDERING INFORMATION

### FOR 12 VOLT LIGHTS

Description	Visibility Arc	Display Pkg. - 5 Cards	Std. Pkg. - 1 Pc.	Visibility Miles	Replacement Bulb
		1 Pc. per Card	OEM Pkg. - 10 Pcs.		
Bi-Color Light	225°	200 BT DP1	200 BT 12V	2	375 12V 25W
Red Side Light	112-1/2°	200 PT DP1	200 PT 12V	2	375 12V 25W
Green Side Light	112-1/2°	200 SDT DP1	200 SDT 12V	2	375 12V 25W
White Masthead Light	225°	200 MT DP1	200 MT 12V	3	375 12V 25W
White Stern Light	135°	200 SNT DP1	200 SNT 12V	2	375 12V 10W
Yellow Towing Light	135°	200 TWT DP1	200 TWT 12V	2	375 12V 10W

### FOR 24 VOLT LIGHTS

Replace the "DP1" with "DP2" For Display Package or the "12V" with "24V" For Standard Package or OEM Package (e.g., 200 BT DP2 or 200 BT 24V). For the Replacement Bulb, Replace the "12V" with "24V" (e.g., 375 24V 25W).

### FOR 32 VOLT LIGHTS

Replace the "DP1" with "DP3" For Display Package or the "12V" with "32V" For Standard Package or OEM Package (e.g., 200 BT DP3 or 200 BT 32V). For the Replacement Bulb, Replace the "12V" with "32V" (e.g., 375 32V 25W).



Fig. 200 SNT



Fig. 200 TWT



Fig. 200 PT



Fig. 200 BT



Fig. 200 SDT

### FIG. 200 SERIES TOP MOUNT