

PLICORD® CON-AG® WATER S & D

WATER SUCTION & DISCHARGE HOSE



- APPLICATION:** Con-Ag® hose is a general purpose water suction and discharge hose for applications in medium or heavy operations such as construction or agriculture.
- CONSTRUCTION:**
- TUBE:** Black Versigard®
 - REINFORCEMENT:** Spiral plied synthetic fabric with wire helix
 - COVER:** Black Versigard® (Wrapped Finish) with yellow spiral stripe
- TEMPERATURE:** -40°F to 180°F (-32°C to 82°C)
- PACKAGING:** 100' lengths, coiled and polywrapped
- BRANDING:** Continuous spiral brand example "Con-Ag Water S & D by Goodyear™."
- COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.
- NON-STOCK/SAMPLES:** 400' minimum order for color change or special branding
- ORDER CODES:** 542-159

NOM. ID		NOM. OD		MAX. WP		BEND RADIUS		VACUUM HG		WEIGHT	
in.	mm.	in.	mm.	psi	Mpa	in.	mm.	in.	mm.	lb./ft.	kg./m
1 1/4	31.75	144/64	42.86	125	.86	4	102	29	736.6	.66	.98
1 1/2	38.10	160/64	49.21	125	.86	4	102	29	736.6	.76	1.13
2	50.80	229/64	62.31	125	.86	7	178	29	736.6	1.03	1.54
2 1/2	63.50	31/64	76.60	100	.70	10	254	29	736.6	1.51	2.25
3	76.20	332/64	88.90	100	.70	14	356	29	736.6	1.78	2.65
4	101.60	435/64	115.50	75	.52	18	813	29	736.6	2.48	3.70
6	152.40	639/64	167.88	75	.52	24	1168	29	736.6	4.48	6.68

Let us help with those hard to find items !



Chemical Transfer
 Cleaning Equipment
 Food
 Hydraulic
 Marine
 Abrasive & Corrosive
 Bulk Transfer
 Cement & Concrete
 Mining
 Aircraft
 Dispensing
 Dock
 Petro Transfer
 Special Application
 Spray
 Steam
 Vacuum
 Washdown
 Water Discharge
 Water Suction & Discharge