

Linemen's Belts & Straps

NOTE: Unless otherwise indicated Vulcanized Fiber Tape Holders are furnished on all belts.



NO. 104

Light weight installers belt with 4" wide, 4 ply cotton body pad, tool loops riveted to 1 3/4" wide nylon belt strap. Belt furnished with circle "D" rings. Complete with harness ring, integral tab and tape holder. Brass grommet reinforced buckle holes accommodate single tongue buckle. Body pad lined—no exposed rivets on inside.



NO. 103

Light weight installers belt with 4" wide 4 ply cotton body pad, harness leather tool loops riveted to 1 3/4" wide nylon belt strap. Belt furnished with circle "D" rings. Complete with harness ring, integral tabs and tape holder. Body pad lined—no exposed rivets on inside. Double pass friction type buckle.



SERIES 150

Pole Straps are made with all nylon webbing, resin treated for abrasion. Material is doubled entire length, and lock stitched. Material has tensile strength of 10,000 pounds. This strap is preferred by many, because there are no buckle holes to weaken the material. Fitted with drop forged steel friction type slide buckle with leather buckle pad.

NOTE: Series 150 Straps are fitted with drop forged steel slide buckle, designed not to slip. Length of straps is easily adjusted. There are no buckle holes on these straps.

NOTE:

Series 150, and 140 are available in the following lengths.
 1 3/4" x 50" (Fixed length, non-adjustable)
 1 3/4" x 56" (Fixed length, non-adjustable)
 1 3/4" x 60" 1 3/4" x 78"
 1 3/4" x 5'6" 1 3/4" x 7'
 1 3/4" x 70" 1 3/4" x 8'
 Please specify when ordering, otherwise 70" straps will be furnished.



SERIES 140 STRAP

This very popular strap is made with materials especially designed for pole climbers. The solid woven nylon fabric is neoprene coated for oil resistance and outdoor use, and has a tensile strength of 3500 pounds. The strap features a red yarn center which acts as a danger signal. When surface has worn to expose the red center the strap should be replaced. Strap is 1 3/4" wide, is fitted with single tongue drop forged steel buckle and drop forged steel snap hooks. Buckle and snap hook ends are reinforced with metal liners.

NOTE:

Series 150, and 140 are available in the following lengths.
 1 3/4" x 50" (Fixed length, non-adjustable)
 1 3/4" x 56" (Fixed length, non-adjustable)
 1 3/4" x 60" 1 3/4" x 78"
 1 3/4" x 5'6" 1 3/4" x 7'
 1 3/4" x 70" 1 3/4" x 8'
 Please specify when ordering, otherwise 70" straps will be furnished.

HOW TO ORDER SIZES

To assure correct fit of Linemen's Belts, refer to table below.

DISTANCE								
Between Dees . . .	19"	20"	21"	22"	24"	26"	28"	30"
BELT SIZE	34"	36"	38"	40"	42"	44"	46"	48"

Belts adjust 4 1/2" each way from center hole.
 For comfort, Dees must not rest on hipbones, but 1" in front, each side.
 For correct Tool Belt size, add 2" to distance (around back) between hipbones.