

# Linemen's Belts & Straps

**NOTE:** Unless otherwise indicated Vulcanized Fiber Tape Holders are furnished on all belts.

## What You Should Know About Linemen's Belts and Straps

Linemen's belts and straps are designed and manufactured in accordance with E.E.I. and OSHA specifications on the date of shipment from the point of manufacture.

Buckles exceed the 2000# tensile test requirements, are drop forged steel and are cadmium plated.

"D" rings and snaphooks are drop forged steel, and cadmium plated. Units will withstand a 5000# tensile test without failure.

Belts are assembled with hand set solid copper rivets and burrs. Only hot waxed nylon thread is used, lock stitched with 5 to 7 stitches per inch.

When ordering belts, check the size chart on page 15.

Belts are priced without holsters. Refer to page 13 for the holster of your choice.



### NO. 106 BELT

Installers belt with 3½" wide body pad. The 1¾" wide belt strap is riveted directly to pad and forms tool loops. Body pad and belt strap nylon fabric impregnated with neoprene. Belt strap 6 ply, contrasting red center. Body pad is lined to provide a body pad with no exposed rivets on inside. Belt is complete with knife snap, tape holder and integral tabs.



### NO. 101 BODY BELT

This very popular belt provides floating feature for body movement and full use of tool loops. Waist strap is 1¾" wide 6 ply neoprene impregnated nylon fabric. 4½" wide neoprene impregnated nylon body pad is lined and padded to provide dielectric feature. 4½" body pad tapers to 3½" at circle "D" rings. Single tongue buckle and circle "D" rings are drop forged steel. No exposed rivets on body side of belt. 1½" leather tool loops are riveted to body strap. Belt is fitted with tape holder, knife snap, harness ring, rings for belt support.



### NO. 108 BELT

Installers belt with 4" wide body pad. The 1¾" wide belt strap is riveted directly to pad and forms tool loops. Body pad and belt strap nylon fabric impregnated with neoprene. Belt strap 6 ply, contrasting red center. Body pad lined to provide a body pad with no exposed rivets on inside. Belt is complete with knife snap, tape holder and integral tabs.



### NO. 102 FULL FLOATING BODY BELT

This belt provides maximum body movement for greater comfort and utilization of tool loops. Waist strap is 1¾" wide 6 ply neoprene impregnated nylon fabric. Body pad is neoprene impregnated nylon 4½" wide and is lined and padded to provide dielectric feature. No exposed rivets on body side of belt. Single tongue buckle and circle "D" rings are drop forged steel. Belt is fitted with tape holder, knife snap, harness ring, rings for belt support.